Sussex (Konecta)
Transportable Mobile Home

∡14°

0,01

Roof

1. OSB 15 mm
2. Ventilation spaceslat 45x50mm
3. Windcloth
4. Frame 45x145 between rockwool 150mm
5. Vapor barrier film
6. Space slat 30 x 50 mm
7. Ceiling boards 11 x 88 mm STV

Laminated purlin 2x80x320 mm

14°

2906

2000

840

2218

0,00

External wall

1. Paneling 20 x 133 mm
2. Ventilation slat 22 x 50 mm
3. OSB 12 mm
4. Frame 45 x 95 mm + rockwool 150 mm
5. Vapor barrier film
6. Spaceslat 45 x 50 mm + rockwool 50 mm
7. Plasterboard 13 mm

1. Floor board 28x87 mm
2. Frame 45 x 145 mm + rockwool 150 mm
3. OSB 10 mm

13592

1080 | 204 | 5924 | 133 | 2011 | 133 | 2011 | 133 | 2773 | 204 | 500

500
204
2814
6092
2737
204
500

A2 600/800   A2 600/800

A1 1200/1200

1775

A1 1200/1200

SU 780/2080   SU 780/2080

SU 780/2080

907

SU 780/2080

SU 780/2080   SU 780/2080

East

DU 1500/2030

SU 780/2080

2175

A1 1200/1200

1375

A3 800/1200   A1 1200/1200   A4 1200/1000   VU 900/2030   A1 1200/1200   A1 1200/1200

4201   133   1500   133   3152   1230   2461

133

1280

2808   204   133   3832   204   500

Sussex (Konecta) Transportable Mobile Home

Insulation

All floor, wall and roof panels are insulated with 100mm Rockwool insulation as standard. Kingspan or other insulation materials are available on request.

Complete Wall Sections

A typical cavity wall construction, built to European Standards for winter temperatures –20°C:

It comprises of :

- T&G cladding 20x180 mm
- 14x50 mm ventilation battens
- OSB 12 mm, timber frame 45x95 mm
- Insulation 100 mm
- Option of internal plasterboard 13mm
- Option of internal cladding 20mm
- Outer cladding is stained with ultra

Metal Profiled Roof tiles

Heavy duty industry standard profiled steel sheet roof tiles are also available to withstand harsh

Sussex (Konecta)
Transportable Mobile Home

The Konecta House is half completed at the factory phase, the external timber colour which you choose, is ready painted for you using quality Remmers protector. We offer a choice of exterior timber profiles in round or square log finish and for interior finishes, you may go for the traditional all wood look, or perhaps you prefer plasterboard which you can paint in your choice of colour, alternatively you may choose a half wood, half plasterboard finish which is very eye catching.

All glass window units used in windows and doors are double-glazed, argon gas filled for complete warmth and quality.
The Konecta House delivered to you flat packed, its construction is done in simple stages I

We offer a range of options for fitting the Konecta House:
1. Fully fitted out and delivered to site.
2. Full Turn Key Offering (Only available on sales of multiple units)
3. Full Erection Service.
4. Option of Mobile or Static Build.
5. Erected to weather-proofed stage, leaving the customer to finish internal stage.
6. Supply Only for Self Build.